


USE LIFTING KEY(S):

- 190668 (RMA57) 610mm LONG
- 190667 (RMA56) 467mm LONG
- 190666 (RMA55) 381mm LONG
- C50 (RMA62) 152mm LONG



VALIANT C250 – 40T DUCTILE IRON MANHOLE COVER & FRAME
WITH INTEGRAL SINGLE SEAL

SAP CODE STANDARD	CODE STANDARD	SAP CODE WITH 2 SLOT HD COUNTERSUNK S/S SCREWS	SAP CODE WITH 4 SLOT HD COUNTERSUNK S/S SCREWS	BS EN124 CLASS	CLEAR OPENING A x B	OVER BASE C x D	DEPTH E	COVER MASS kg	TOTAL MASS kg	
CCVA76HK	C5144	186022	186023	C250(40T)	600 x 450	760 x 610	100	57	89	
CCVA77HK	C5145	204116	212358	C250(40T)	600 x 600	760 x 760	100	71	107	
	186025	C5146	186026	–	C250(40T)	750 x 600	910 x 760	100	85	127
	172789	C5148	186028	186029	C250(40T)	900 x 600	1060 x 760	100	100	147

SECURITY VERSION CODES WERE PREVIOUSLY SUFFIXED WITH /L2 & /L4 FOR 2 OR 4 SCREWS RESPECTIVELY FOR AREAS WHICH ARE NOT SUBJECT TO CONTINUOUS THROUGH TRAFFIC eg CAR PARKS, LOADING BAYS etc.
Note: these products are tested to 40 tonne test load & may be used in areas open to access by slow moving HGV's

SEAL SYSTEM IS DESIGNED TO PREVENT THE EGRESS OF ODOURS WHEN THE SEALING GROOVE IS FILLED WITH A SUITABLE SEALING MEDIUM (IE. WATERPROOF GREASE)
NB. THIS IS NOT A PRESSURE TIGHT SEAL

COPYRIGHT and DESIGN RIGHT
This drawing is the exclusive property of Saint Gobain PAM UK and is confidential and must not be reproduced or disclosed to any third party without written consent.
It must be used only for the purpose for which it has been issued and is returnable on request.

Produced at Holwell Works in UK



GROUP	CLASS	APPLICATION	KITEMARK	DRAWN	DATE FIRST ISSUED	DRAWING TITLE	ISSUE
3	EN124 C250 40T Test			JNP SCALE NTS	02/08/05 DATE THIS ISSUE 08/01/14	VALIANT C250-40T	8

The information on this sketch is, to the best of our knowledge correct at the time of printing. However Saint-Gobain are constantly looking at ways of improving their products and services and therefore reserve the right to change, without prior notice, any of the data shown. Any orders placed will be subject to our Standard Conditions of Sale, available on request.