





# Product Data Sheet

UNICLASS L7315	
Cl/Sfb	(52.6)
March 2014	R1

## VX-F030 Square Grating Nickel Bronze



### 150x150mm Square Grating (NPSM threaded or Direct Fit)

GEN code	Material	FIT	Finish		A	B	C	WTKG	Grating free area (cm )
VX-F030	Nickel Bronze	NPSM	Standard 227101	Polished 234174	150	57	110	1.3	119
VX-F030	Nickel Bronze	Direct Fit	Standard 233408	Polished 234175	150	57	110	1.3	119

## General Description

150 x 150mm square nickel bronze grating with a NPSM thread or plain spigot for direct fit. Supplied in a standard finish or in a polished finish to order.

## Technical Specification

**Material:** Nickel bronze  
**Loading :** K3

## Compatible Items

**NPSM grating:** All cast iron Floor gullies VX-F200, VX-F210, VX-F220, VX-F230  
 Raising pieces VX-F350

**Direct fit grating:** Pipework 110mm OD  
 Ensign, EEZI-FIT, Timesaver 416 , other materials 110mm OD  
 Timesaver 437 using a stepped coupling TD02

**Options**  
 Removable bottle trap VX-F400  
 Filter basket VX-F410  
 Accessories Oval /circular funnels VX-F305, VX-F300  
 Security screws (bag of 4) VX-F420

## Flowrate@ 20mm head

**Fitted to Medium Sump Gully**  
**Fitted to P Trap**  
**Fitted to S Trap**

= 2.6 L/s  
 = 2.0 L/s  
 = 1.7 L/s



Saint Gobain PAM  
 Lows Lane, Stanton-by-Dale  
 Ilkeston, Derbyshire, DE7 4QU  
 Sales : 0115 930 0630

Technical T:01952 262 529 F: 01952 262 592  
 E: technical.soildrain.uk.pam@saint-gobain.com

\* PLEASE NOTE: At the time this data sheet was prepared all the data shown was accurate at the time of release.