



SECTION X-X

WATERSHED HR880

SAP CODE	STANCAD CODE	EN124 LOADING	KITEMARK	CLEAR OPENING A x B	BASE SIZE C x D	DEPTH E	WATERWAY AREA sqcm	HA 102/00 GRATE TYPE	MASS kg
187140	HR880 1	C250	YES	380 x 400	525 x 490	75	940	S	28

Manufactured in ductile iron to BS EN124 class C250 with non-rock captive hinged grating.
 For use in city roads carrying continuous heavy traffic.

COPYRIGHT and DESIGN RIGHT
 This drawing is the exclusive property of Saint Gobain PAM UK and is confidential and must not be reproduced or disclosed to any third party without written consent.
 It must be used only for the purpose for which it has been issued and is returnable on request.

Produced at Holwell
 Works in UK



CLASS	APPLICATION	GROUP	KITEMARK	DRAWN	DATE FIRST ISSUED	DRAWING TITLE	ISSUE
EN124 C250	 	3		JNP	06/02/06	WATERSHED C250 KERB HINGED	6
				SCALE NTS	DATE THIS ISSUE 27/01/14		

The information on this sketch is, to the best of our knowledge correct at the time of printing. However Saint-Gobain are constantly looking at ways of improving their products and services and therefore reserve the right to change, without prior notice, any of the data shown. Any orders placed will be subject to our Standard Conditions of Sale, available on request.